



## **Digital Blocks Expands Video Signal & Image Processing IP Core Family**

*The Digital Blocks new Video Signal & Image Processing IP Cores include a Color Space Converter, Chroma Resampler, CCIR BT.656 Encoder & Decoder, and system-level IP for RGB-to-CCIR 601/656 conversion.*

**GLEN ROCK, New Jersey, January 31, 2012** – Digital Blocks, a leading developer of silicon-proven semiconductor Intellectually Property (IP) soft cores for system-on-chip (SoC) ASIC, ASSP, & FPGA developers with Embedded Processor & Peripherals, Networking, Display Controller, Display Link Layer, 2D Graphics, and Audio / Video processing requirements, today announces six IP Core additions to the Video Signal & Image Processing family.

Digital Blocks' *Video Signal & Image Processing IP Core Family* includes the following:

### DB1800 - Standard Definition NTSC/PAL/SECAM Video Sync Separator

Digital Blocks DB1800 Video Sync Separator IP Core extracts timing information from a standard NTSC/PAL/SECAM composite sync video signal, extracting horizontal sync, vertical sync, chroma burst / back porch, and field 1 (odd) or field 2 (even) detection.

### DB1810 - Color Space Converter

Digital Blocks DB1810 Color Space Converter IP Core transforms three color components between 10+ color spaces.

### DB1820 - Chroma Resampler

Digital Blocks DB1820 Chroma Resampler IP Core down converts 4:4:4 Y'CbCr to 4:2:2 Y'CbCr in accordance with the ITU-R BT.601 standard requirements. Includes image rejection filter.

### DB1825 - RGB to Y'CbCr Color Space Convert with 4:4:4 to 4:2:2 Chroma Resampler

Digital Blocks DB1825 Color Space Converter & Chroma Resampler IP Core transforms 4:4:4 sampled RGB color components to 4:4:4 Y'CbCr color space followed by Chroma Resampling to 4:2:2 Y'CbCr color components (combined DB1810 and DB1820 products).

### DB1830 - BT.656 Encoder

Digital Blocks DB1830 CCIR 656 Encoder IP Core encodes 4:2:2 Y'CbCr component digital video with synchronization signals to conform to NTSC & PAL video ITU-R BT.656 digital coding standard.

### DB1840 - BT.656 Decoder

Digital Blocks DB1840 CCIR 656 Decoder IP Core decodes a ITU-R BT.656 digital framed signal into 4:2:2 Y'CbCr component digital video with synchronization signals.

### DB1892 - RGB to CCIR601/656 Encoder

Digital Blocks DB1892 RGB to CCIR 601 / CCIR 656 Encoder IP Core interfaces RGB data along with synchronization signals from a LCD Controller (such as Digital Blocks' DB9000IP, or any LCD display timing & control unit) to a TFT LCD Panel by-way-of a CCIR 601 / CCIR 656 interface.

### **Price and Availability**

The *Video Signal & Image Processing IP Core Family* is available immediately in synthesizable Verilog along with synthesis scripts, a simulation test bench with expected results, installation guide, and a technical user manual. For further information, product evaluation, or pricing, please visit Digital Blocks at <http://www.digitalblocks.com>

### **About Digital Blocks**

Digital Blocks designs silicon-proven IP cores for technology systems companies, reducing customer's development costs and significantly improving their time-to-volume goals. Digital Blocks is located at 587 Rock Rd, Glen Rock, NJ 07452 (USA).

Phone: +1-201-251-1281; eFax: +1-702-552-1905; Media Contact: [info@digitalblocks.com](mailto:info@digitalblocks.com);

Sales Inquiries: [info@digitalblock.com](mailto:info@digitalblock.com); On the Web at [www.digitalblocks.com](http://www.digitalblocks.com)

###

Digital Blocks is a registered trademark of Digital Blocks, Inc.

Intel is a registered trademark of Intel Corporation